


## 121 Winkel 45°, ISO/EN A4/45°

EN	S/V	Dim. [inch]	Code	a [mm]	b [mm]	z [mm]
•	S	3/8	770 121 103	20	26	10
•	V	3/8	770 121 203	20	26	10
•	S	1/2	770 121 104	22	28	9
•	V	1/2	770 121 204	22	28	9
•	S	3/4	770 121 105	25	32	10
•	V	3/4	770 121 205	25	32	10
•	S	1	770 121 106	28	39	11
•	V	1	770 121 206	28	39	11
•	S	1 1/4	770 121 107	33	43	14
•	V	1 1/4	770 121 207	33	43	14
•	S	1 1/2	770 121 108	36	46	17
•	V	1 1/2	770 121 208	36	46	17
•	S	2	770 121 109	43	55	19
•	V	2	770 121 209	43	55	19
-	S	2 1/2	770 121 110	46	54	19
-	V	2 1/2	770 121 210	46	54	19
-	S	3	770 121 111	52	61	22
-	V	3	770 121 211	52	61	22



## 130 T-Stück, egal, ISO/EN B1

EN	S/V	Dim. [inch]	Code	a [mm]	z [mm]
•	S	1/8	770 130 101	19	12
•	V	1/8	770 130 201	19	12
•	S	1/4	770 130 102	21	11
•	V	1/4	770 130 202	21	11
•	S	3/8	770 130 103	25	15
•	V	3/8	770 130 203	25	15
•	S	1/2	770 130 104	28	15
•	V	1/2	770 130 204	28	15
•	S	3/4	770 130 105	33	18
•	V	3/4	770 130 205	33	18
•	S	1	770 130 106	38	21
•	V	1	770 130 206	38	21
•	S	1 1/4	770 130 107	45	26
•	V	1 1/4	770 130 207	45	26
•	S	1 1/2	770 130 108	50	31
•	V	1 1/2	770 130 208	50	31
•	S	2	770 130 109	58	34
•	V	2	770 130 209	58	34
•	S	2 1/2	770 130 110	69	42
•	V	2 1/2	770 130 210	69	42
•	S	3	770 130 111	78	48
•	V	3	770 130 211	78	48
•	S	4	770 130 112	96	60
•	V	4	770 130 212	96	60