


Zubehör für Push-In Fittings

3130 Sicherheitsverschluss-Clip


Technisches Polymer



ØD							H	K	Kg
4	3130 04 01	3130 04 02	3130 04 03	3130 04 04	3130 04 05	3130 04 10	6,6	3	0,001
6	3130 06 01	3130 06 02	3130 06 03	3130 06 04	3130 06 05	3130 06 10	7,8	3,1	0,001
8	3130 08 01	3130 08 02	3130 08 03	3130 08 04	3130 08 05	3130 08 10	9,5	4,3	0,001
10	3130 10 01	3130 10 02	3130 10 03	3130 10 04	3130 10 05	3130 10 10	10,8	4,2	0,002
12	3130 12 01	3130 12 02	3130 12 03	3130 12 04	3130 12 05	3130 12 10	12,5	5,1	0,003
14	3130 14 01	3130 14 02	3130 14 03	3130 14 04	3130 14 05	3130 14 10	15	6	0,004

CLIP Cliqueteile für Schläuche und Fittings

Technisches Polymer




ØD		Anzahl Anschlüsse	H	K	N	Kg
4	CLIP 04 00	8	9	13,5	10,5	0,007
6	CLIP 06 00	8	10,5	13	10,5	0,008
8	CLIP 08 00	7	12,5	10,5	12	0,007
10	CLIP 10 00	6	14	12	15	0,005
12	CLIP 12 00	5	16,5	14	16,5	0,009
14	CLIP 14 00	4	18	16	20,5	0,009

Verpackungseinheiten à 10 Stück desselben Durchmessers (inkl. Schlauchbinder 9,5 mm Länge).

3000 Demontage-Werkzeug

Behandelter Stahl



	H	H1	L	Kg
3000 70 00	25	20	96	0,021

Zum Lösen von Schläuchen und Fittings LF 3000® an schwer zugänglichen Stellen empfehlen wir den Einsatz eines Demontagewerkzeugs.

3110 Kodierringe für Löseringe


Technisches Polymer



ØD						Kg
4	3110 04 00	3110 04 02	3110 04 03	3110 04 04	3110 04 05	0,001
6	3110 06 00	3110 06 02	3110 06 03	3110 06 04	3110 06 05	0,001
8	3110 08 00	3110 08 02	3110 08 03	3110 08 04	3110 08 05	0,001
10	3110 10 00	3110 10 02	3110 10 03	3110 10 04	3110 10 05	0,001
12	3110 12 00	3110 12 02	3110 12 03	3110 12 04	3110 12 05	0,001
14	3110 14 00	3110 14 02	3110 14 03	3110 14 04	3110 14 05	0,002

0178 Reduziernippel, Innen-/Außengewinde BSP und metrisch

Messing vernickelt, NBR




C1	C2		E	F	L	Kg
M7x1	M5x0,8	0178 55 19	5	10	12	0,005
G1/8	M5x0,8	0178 10 19	5	13	9	0,005
G1/4	G1/8	0178 13 10	5,5	16	9,5	0,006
G3/8	G1/8	0178 17 10	5,5	20	10,5	0,016
	G1/4	0178 17 13	5,5	20	10,5	0,011
G1/2	G1/4	0178 21 13	7,5	24	12,5	0,024
	G3/8	0178 21 17	7,5	24	12,5	0,016
G3/4	G1/2	0178 27 21	7,5	32	13,5	0,035

mit integriertem Dichtungsring

0222 Verschlusschraube mit Innensechskant, Außengewinde BSP und metrisch

Messing vernickelt, NBR



C		E	F	F1	H	Kg
M5x0,8	0222 19 00	3,5	8	2,5	7	0,002
M7x1	0222 55 00	5	10	3	8,5	0,003
G1/8	0222 10 00	5	13	5	8,5	0,006
G1/4	0222 13 00	5,5	16	6	9,5	0,010
G3/8	0222 17 00	5,5	20	8	10,5	0,019
G1/2	0222 21 00	7,5	24	10	12	0,031

mit integriertem Dichtungsring