



TS270, Muffe

- Edelstahl
- EPDM O-Ring
- T-min. = -20°C, T-max. = 90°C, P-max. = 16bar
- Lösbar



Artikel-Nr.	Abmessung	GTIN			
TS27015	15	5022050251152			
TS27018	18	5022050251190			
TS27022	22	5022050251220			
TS27028	28	5022050251251			
TS27035	35	5022050251275			
TS27042	42	5022050251299			
TS27054	54	5022050251312			



TS270S, Schiebemuffe ohne Anschlag

- Edelstahl
- EPDM O-Ring
- T-min. = -20°C, T-max. = 90°C, P-max. = 16bar
- Lösbar



Artikel-Nr.	Abmessung	GTIN			
TS270S15	15	5022050251428			
TS270S18	18	5022050251459			
TS270S22	22	5022050251480			
TS270S28	28	5022050251510			



TS243, Reduziernippel

- Edelstahl
- EPDM O-Ring
- T-min. = -20°C, T-max. = 90°C, P-max. = 16bar
- Lösbar



Artikel-Nr.	Abmessung	GTIN			
TS2431815	18 x 15	5022050254252			
TS2432215	22 x 15	5022050254283			
TS2432218	22 x 18	5022050254313			
TS2432815	28 x 15	5022050254368			
TS2432818	28 x 18	5022050254399			
TS2432822	28 x 22	5022050254429			
TS2433522	35 x 22	5022050254528			
TS2433528	35 x 28	5022050254542			
TS2434222	42 x 22	5022050254580			
TS2434228	42 x 28	5022050254603			
TS2434235	42 x 35	5022050254627			
TS2435435	54 x 35	5022050254702			
TS2435442	54 x 42	5022050254726			



TS301, Kappe

35 bis 54mm mit TDX-Demontagehülse

- Edelstahl
- EPDM O-Ring
- T-min. = -20°C, T-max. = 90°C, P-max. = 16bar
- Lösbar



Artikel-Nr.	Abmessung	GTIN			
TS30115	15	5022050258670			
TS30118	18	5022050258717			
TS30122	22	5022050258755			
TS30128	28	5022050258786			
TS30135	35	5022050258809			
TS30142	42	5022050258823			
TS30154	54	5022050258847			