


## 92 Dichtkopf mit BSP-Überwurfmutter



BS5200-A – DKR



Bestell-Nr.	Schlauch ID				Gewinde BSP	A mm	B mm	W mm
	DN	Zoll	Size	mm				
39282-4-4	6	1/4	-4	6,4	1/4x19	33	14	17
39282-4-4B	6	1/4	-4	6,4	1/4x19	36	16	17
39282-6-4B	6	1/4	-4	6,4	3/8x19	37	18	22
39282-6-6	10	3/8	-6	9,5	3/8x19	37	14	19
39282-8-8	12	1/2	-8	12,7	1/2x14	42	15	27
39282-8-8B	12	1/2	-8	12,7	1/2x14	46	19	27
39282-10-10	16	5/8	-10	15,9	5/8x14	53	16	30
39282-10-10B	16	5/8	-10	15,9	5/8x14	55	18	30
39282-12-12	19	3/4	-12	19,1	3/4x14	58	21	32
39282-16-16B	25	1	-16	25,4	1x11	57	21	41

## B1 Dichtkopf mit BSP-Überwurfmutter 45° Bogen

BS 5200-D – DKR 45°



Bestell-Nr.	Schlauch ID				Gewinde BSP	A mm	B mm	E mm	W mm
	DN	Zoll	Size	mm					
3B182-4-4	6	1/4	-4	6,4	1/4x19	51	32	16	17
3B182-6-6	10	3/8	-6	9,5	3/8x19	58	35	17	19
3B182-6-6B	10	3/8	-6	9,5	3/8x19	58	35	17	19
3B182-8-8	12	1/2	-8	12,7	1/2x14	68	41	19	27
3B182-8-8B	12	1/2	-8	12,7	1/2x14	67	41	19	27
3B182-10-10	16	5/8	-10	15,9	5/8x14	81	45	21	30
3B182-12-12	19	3/4	-12	19,1	3/4x14	92	55	27	32
3B182-16-16	25	1	-16	25,4	1x11	107	71	33	41

Auch in Edelstahl erhältlich. Details siehe CAT 4400.1/DE

Geprüfte **Armaturenserie** für Schlauchtypen:

B: Messing

82 801Plus 801RH 804 821FR 830M 836 837BM 837PU 838M 846